



Model: <u>LP051</u> 7.4V/ 1400mAh/20C

## **Specifications**



Item		(mm)	(inch)		
Pack	Thickness	13.5.0-0.5	0.53-0.01		
Dimension	Width	17.5-0.5	0.69-0.02		
	Length	167.5-0.5	6.59-0.02		
Weight	Gram	Approx. 73	orox. 73		
	Ounce	Approx. 2.59			

Nominal Capacity <sup>(1)</sup>		1400mAh	
Nominal Voltage <sup>(2)</sup>		7.4V	
Impedance at 1khz		Max. 50m $\Omega$	
Charge	Current	Max. 2.8A (2C)	
	Voltage	Max. 8.5V	
Discharge	Continuous Current	Max. 28.0A(20C)	
	Burst Current	Max. 52.0A(40C)	
	Voltage cut-off	6.0V	
Cycle Life	1C/1C	200 cycle	
80% Retention	1C/50C	50 cycle	
Self-discharge		<8% per month	
Operating	Charge	0°C~45°C	
Temperature	Discharge	-20℃~60℃	
Range	Storage	-20℃~40℃	

<sup>(1)</sup>Nominal capacity (average discharge capacity): discharge current 0.5C, end of voltage 6.0V, temperature 23  $\pm 2^{\circ}\text{C}$ .

## **High Rate Discharge Curves (12A)**

OPV	Cut-off	Duration	ADV	Current	Capacity	Power
mv	mv	min	mv	Α	AH	WH
7455	5978	5.98	6707.74	-12.04	1.20	8.06



The information in this document is based on documents issued in February, 2011 at the latest.

The information is subject to change without notice. For actual design-in refer to the latest publication of data sheet, etc., the most up-date specifications of the device.

<sup>(2)</sup> Nominal voltage (average discharge voltage): discharge current 0.5C, end of voltage 6.0V, temperature 23  $\pm$  2°C.